



COMPONENTS

SPECIAL THINNERS FOR K-FLEX ADHESIVES



Before covering the surfaces to be insulated, it is advisable to clean them with the special K-FLEX thinners which, thanks to its composition, is also suitable for use with K 414, K 420 or K 425 adhesives. Cleaning of all surfaces with the special K-FLEX thinners also improves the performance of the adhesives. The special K-FLEX thinners can be also used for cleaning brushes and spatulas used to spread the glue.

Available in 1 litre tins.



COMPONENTS

K-FLEX GLUES

INDICATED CONSUMPTION OF 1 LITRE OF ADHESIVE



K-FLEX K 414, K 420 and K 425 glues have been specifically designed for use with K-FLEX elastomeric foam insulation material.

The securely bonded surfaces and joints are resistant to ageing and atmospheric agents, and preserve the technical characteristics of the insulating material.

K 414 ADHESIVE in tins of: 0.5 - 0.8 - 2.6 litres

K 420 ADHESIVE in tins of: 0.26 - 1 - 2.6 litres

K 425 ADHESIVE in tins of: 0.85 litre (complete with glue activator)

TUBES	GLUED TO THE HEADS	GLUED LENGTHWAYS
thickness mm 9	every 1,350 m	every 150 m
thickness mm 13	every 500 m	every 100 m
thickness mm 19	every 300 m	every 80 m
thickness mm 25	every 220 m	every 60 m
thickness mm 32	every 180 m	every 40 m
thickness mm 40	every 139 m	every 27 m

SHEETS: 1 litres every 7m²

L'ISOLANTE K-FLEX does not accept responsibility for different values to those indicated.

COMPONENTS

K-FINISH PAINT



K-FINISH is a water-based paint for coverings on internal and external installations insulated with K-Flex materials.

With its polymerized acrylic base, it does not pollute and does not give off odours, and is particularly recommended for all indoor uses. Quick drying, it offers excellent protection. Coats of white paint, applied over a layer of K-FINISH will maintain their colour even in dark environments. The colours are resistant to light.

It is advisable to paint the surface of externally insulated pipes to protect them against harsh weather conditions and UV rays. For further protection it is advisable use a double layer of K-FINISH paint. Available in 2.5 litre tins, and on request, in various colours.

COMPONENTS

K-FLEX COLOR PAINT - Coloured water-based paint for retouching



Special paint for retouching the surfaces of COLOR coverings, scratched or damaged during installation. The paint, ready for use, should be applied with a soft brush.

Available in 0.5 litre tins.

range of 8 stock colours:

	RAL 5012 blue		RAL 3000 red
	RAL 6032 green		RAL 9011 black
	RAL 7035 grey		RAL 1019 sand
	RAL 9002 white		RAL 3015 pink

COMPONENTS

K-FLEX ADHESIVE DISPENSER



A useful accessory that controls flow and helps spread adhesives evenly on insulation surfaces, avoiding having to continuously dip the brush into the tin of adhesive.

The adhesive correctly diluted, is manually pumped through the brush.